

All-in-one Touchscreen PC from Shuttle

The Shuttle X502VA is an all-in-one PC boasting a 39.6cm (15.6-inch) touchscreen LCD powered by Intel's Atom D510 dual-core processor. It is fully configured with 2 GB of memory, a 250 GB hard disk drive and runs OpenSUSE Linux. Equipped with Intel's GMA 3150 onboard graphics, it provides generous performance for daily computing with internet and office applications. A webcam, built-in speakers, card reader, WLAN and other features leave nothing you could ask for. Have any applications start up quickly by just touching the screen for working most swiftly and conveniently.

Feature Highlight

<i>All-in-one design</i>	<ul style="list-style-type: none"> Full featured stylish PC platform Small: 391 x 327 x 36 mm (WHL) Stand can also be used as a handle External, fanless power supply (40W)
CPU & Chipset	<ul style="list-style-type: none"> CPU: Intel ATOM D510 Dual Core Codename: Pineview-D (1,66 GHz) Chipset: NM10 (Platform Controller Hub)
Storage	<ul style="list-style-type: none"> 2 GB DDR2-667 Memory 250 GB SATA hard disk drive (2.5")
Operating system	<ul style="list-style-type: none"> OpenSUSE Linux, powered by Novell
Display & Graphics	<ul style="list-style-type: none"> 39.6cm (15.6") touchscreen (1366x768) Integrated graphics (GMA3150, DX9) VGA Video output (Extended Mode)
Connectivity	<ul style="list-style-type: none"> 4x USB, Audio: Mic, Line-out LAN connector, Wireless LAN (draft-n) Legacy ports: 2x serial, 1x parallel
Built-in	<ul style="list-style-type: none"> SD card reader 1.3 Megapixel webcam 2x 2W speakers, Microphone 100mm VESA mount capable Light bar at the bottom
Power Supply	<ul style="list-style-type: none"> 40W, fanless, Energy Star 5 compliant
Warranty	<ul style="list-style-type: none"> 24 months Pick-up-and-Return Service

Intel
Pineview-D

Shuttle All-in-One PC X502VA



Touchscreen



Dual Core



Fanless



© 2009 by Shuttle Computer Handels GmbH (Germany). All Information subject to change without prior notice. Pictures for illustration purposes only.

EAN Code X502VA White



EAN Code X502VA Black



Images for illustration purposes only.

Shuttle X 50V2-Series – Product Overview (Europe)

Name	Operating System	Hard disk	Memory	Ser/Par Port	Barcode Number
Barebone X50V2	None	None	None	Included as accessory	White: 811686003076 Black: 811686003083
				Built in	White: 811686003113 Black: 811686003090
System X 5020T	Configurable	Configurable	Configurable	Built in	White: - Black: -
System X 5020TA	Windows 7 Home Premium	250 GB	2 GB	Built in	White: 4046047102068 Black: 4046047102075
System X50X2A	None	250 GB	2 GB	Built in	White: 4046047102082 Black: 4046047102099
System X502VA	Linux openSuSe	250 GB	2 GB	Built in	White: 4046047102105 Black: 4046047102112


Shuttle X502VA - Special Product Features



All applications at your fingertips

The innovative touchscreen technology delivers the simplest operation possible and makes the screen the centre of action. Its high-quality design lets you control the whole range of multimedia - music, movies, video playback and web browsers start by just touching the screen.

Intel Atom Dual Core (Pineview-D)



New Atom processor integrates the graphics core

Shuttle X502VA is equipped with Intel's new Atom processor, codenamed Pineview. It brings both the memory controller and graphics core on-die which helps to reduce the thermal output and memory latency. The CPU is connected to the Southbridge NM10, codenamed Tiger Point.

Dual Core. Do more.

The vast majority of the existing netbooks and all-in-one PCs with an Intel Atom CPU use the Single Core version. In contrast to this, Shuttle's all-in-one PC stands out from the crowd with its embedded Intel Atom D510 Dual Core processor, which is boosting the productivity of the PC system, particularly with regards to multithreaded applications.



Power saving

The new X502VA version equipped with Intel Atom D510 Dual-Core processor and eco-friendly ENERGY STAR 5.0 qualified power adapter consumes about 22 Watt in full load mode, which is approximately half as much as with the previous Atom platform with Atom 330 processor and 945GC chipset (X 5000T).



VGA Port

This VGA port can be used to connect a secondary external LCD display or beamer to the PC.



All-in-one PC

Your complete PC system with many components already built in comes in just one single device! This includes the webcam, microphone, mainboard, display, touchscreen input interface, Wireless LAN module and speakers. Saves you more space, looks simply stylish, less wiring.



Built-In Webcam and Microphone

The built-in 1.3 mega pixel webcam and microphone makes it easy to take pictures or stream live images across the Internet – and connect in real-time with friends, family, and colleagues.



Slim and chic

Designed as space-savers, this 15.6 inch all-in-one desktop PC only measures 3.6cm in depth.



Fanless - as quiet as 22dBA

The Shuttle X502VA features a cooling system that combines an integrated heat-sink with thermal pads - and removes the fan. As an added benefit, it's not only quiet but also dust-free.




Carrying handle

Cleverly, the stand can be pulled up to serve as a handle - easy to move and light to carry with one hand.




Kensington Lock

This is a small, metal-reinforced hole as part of an anti-theft system. (The lock-and-cable apparatus is not included.)



VESA mounting

The stand on the rear can easily be removed unveiling four VESA mounting screw holes that can be used for mounting arms and other mounting devices from a variety of manufacturers.



4 Point Touch Screen Calibration


The Shuttle X502VA features a precise touch screen input device. This can easily be calibrated just by pointing four times with the stylus pen on the screen. With this four point calibration, you can use demanding graphical user interfaces (GUI) that require precise cursor control to properly activate small icons, buttons, scroll bars, etc.



Serial and parallel legacy ports

Legacy ports are still a requirement for certain industrial applications. Thus, X502VA provides one parallel and two serial ports at the back panel. (European version)

Shuttle X502VA Overview (Connectors, buttons, etc.)




- 1 Touchscreen LCD display
- 2 Webcam
- 3 Microphone
- 4 Power on LED
- 5 Hard disk LED
- 6 Wireless LAN LED (Wifi)
- 7 Stereo speakers
- 8 Light bar
- 9 Card reader
- 10 4 USB connectors
- 11 LAN connector
- 12 Microphone input
- 13 Audio line out (head phone)
- 14 VGA video output
- 15 Stand (handle)
- 16 Power on button
- 17 Stylus pen with holder
- 18 DC-input for power supply
- 19 Kensington lock
- 20 Vesa mount
- 21 2x COM, 1x Par. Ports



Shuttle X502VA – Range of Applications



Entertainment
Music, Movies,
Photo gallery, TV*
*) TV tuner USB stick
required



Work
Banking, Shopping,
Office, Stock trading



Control
Surveillance,
Home Automation,
Control device



P.O.S.
Point of sales



Education
In schools, at home,
for children and adults



Communication
Email, VoIP, Messenger,
Blog, Video Conferencing



Digital Signage
Visual advertising,
entertainment, displaying
information in public areas

Shuttle X502VA – Specifications

Chassis	Color: white or black Dimensions: 391.3 x 327 x 36 mm (WxHxL) 100mm VESA mount capable Mounting hole for Kensington lock Light bar at the bottom
Operating system	OpenSUSE Linux, powered by Novell
Touch-screen	Touchscreen function support fingertip input Resistance and single touch technology Including stylus pen for the touchscreen
39.6cm (15.6-inch) display	39.6cm/15.6" LCD display, ratio: 16:9 wide screen panel Resolution: 1366x768 = 1.05 Megapixels Adjustable Backlight: CCFL (Cold cathode fluorescent lamp)
Processor	Intel Dual Core Atom processor D510 (Codename: Pineview-D) 45nm manufacturing process, FCBGA559 Intel Hyper-Threading technology: 2-threads per core Intel 64 architecture, Core clock: 1.66GHz, L2 Cache: 1024kB, TDP: max. 15W Integrated North Bridge with controller for memory and graphics
South bridge	Intel® NM10 Platform Controller Hub (PCH), Codename: Tiger Point
BIOS	AMI BIOS in a 8Mb Flash ROM supports PnP, ACPI 3.0 Supports external USB flash memory card boot up
Memory	2 GB DDR2-667 SO-DIMM memory
Hard disk drives	250 GB Serial ATA hard disk in 6.35cm/2.5" format
Card reader	Integrated card reader supports SD, SDHC and SDXC memory flash cards
Webcam	Integrated Webcam module with 1.3 Megapixel resolution
Audio Microphone Speakers	IDT92HD81 Audio Codec with Azalia support, two analog audio connectors (3.5mm): 1) Line out (head phone) 2) microphone input Front panel with integrated Electret Condenser Microphone and 2x 2W speakers

<i>Integrated graphics</i>	<p>The Graphics Processing Unit (GPU) is integrated into the processor</p> <p>Intel GMA 3150, 400MHz render clock frequency</p> <p>Intel Dynamic Video Memory Technology 4.0 (DVMT 4.0)</p> <p>Share system memory max. 256MB</p> <p>Supports DirectX 9 and 2D/3D instruction set, Pixel Shader 2.0</p> <p>MPEG2 hardware acceleration</p> <p>Intel Clear Video / ProcAmp technology allows user adjustment of hue, saturation, brightness and contrast</p> <p>Two display ports:</p> <ul style="list-style-type: none"> - Digital LVDS channel supports up to 1366*768, 18bpp resolution - Analog RGB supports up to 2048*1536, 60Hz resolution - Supports Extended Desktop Mode and Clone Mode
<i>LAN</i>	<p>JMicron JMC261 single-chip PCIe Fast Ethernet combo Card Reader Host controller</p> <p>IEEE 802.3u 100Base-T specification compliant</p> <p>Supports 10/100 MBit/s operation</p> <p>Supports S3 Wake-on-LAN (WOL) feature</p>
<i>Wireless LAN (Wifi)</i>	<p>Supports 802.11 b/g and draft-n</p> <p>Mini PCIe x1 card</p>
<i>Connectors</i>	<p>VGA connector (D-Sub 15 pol., analog)</p> <p>4x USB 2.0 (2x left side, 2x right side)</p> <p>Netzwerk (RJ45)</p> <p>Audio Line-out (head phone)</p> <p>Microphone input</p> <p>2x Serial ports, Parallel port</p> <p>DC input for power supply</p>
<i>LED's and buttons</i>	<p>Power button</p> <p>Power LED (blue)</p> <p>Hard disk LED (orange)</p> <p>Wireless-LAN / Wifi LED (green)</p>
<i>Power supply</i>	<p>Externes 40W Netzteil (lüfterlos), Abmessungen: 27 x 37 x 90 mm</p> <p>Energy Star 5 konform</p> <p>Eingang (Wechselspannung): 100-240V AC, 50-60Hz</p> <p>Ausgang: 19V DC, max. 2,1A</p>
<i>Certifications</i>	<p>Safety certifications: TÜV, CB, BSMI</p> <p>EMI certifications: CE, FCC, BSMI, R&T</p> <p>Other certifications: RoHS, Energy Star 5</p>
<i>Environment</i>	<p>Operating temperature: 0~35°C, Humidity: 0~60%</p>
<i>Warranty</i>	<p>24 months Pick-up-and-Return Service (PUR)</p>

*) System resources and hardware (such as PCI and PCI Express) require physical memory address locations that can reduce available addressable system memory. This could result in a reduction of as much as 1 GB or more of physical addressable memory being available to the operation system and applications, depending on the system configuration and operation system.