# Whisper-quiet Mini PC with an Intel Atom dual-core processor

To put it in a nutshell, the Shuttle XS 3500BA is an extremely slim and ergonomic Mini PC that works highly energy-efficiently. With a power consumption that is barely not worth mentioning, its noise nevel is close to zero. The XS 3500BA has an Intel Atom D510 dual-core processor (2x 1.66 GHz) beating at its heart while also using integrated graphics. Because of its completely fanless case layout, it is virtually maintenance-free and noiseless. The 38mm thin system comes with 2GB memory, a 160GB hard disk with Windows 7 Professional, WLAN (n) and a card reader. It sports an array of connectors too which include 5x USB, VGA, Ethernet and audio ports.

Feature Highlights							
Chassis	<ul> <li>Slim 1.5 litre chassis</li> <li>Dimensions: 25.2 x 16.2 x 3.84 cm</li> <li>Hole for the Kensington Lock</li> <li>Optional: VESA75/100 mounting kit PV01</li> </ul>						
Operating system	Microsoft 7 Professional						
CPU	Intel ATOM D510 Dual Core (Pineview-D)						
Chipset	Intel NM10 Express Chipset						
Graphics	Integrated Intel GMA3150 Graphics						
Memory	2GB DDR2-667 SO-DIMM module						
Storage	<ul><li>160 GB SATA hard disk (2.5")</li><li>With SD card reader</li></ul>						
Connectors and WLAN	<ul> <li>D-Sub VGA</li> <li>5x USB 2.0 (1x front, 4x rear)</li> <li>Microphone input</li> <li>Headphones output (Line-out)</li> <li>LAN</li> <li>WLAN 802.11 b/g/n</li> </ul>						
Power supply	External 40W fanless power supply						
Applications	Basic and Home-Media						



Bestellnummer: PET-XS350BA1

Images are only for illustration purposes. An optical drive is not included.

# System **X53500BA**Ultra-Small-Form-Factor-PC





2010 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice. Pictures for illustration purposes

### Shuttle Ultra-Small-Form-Factor-PC XS 3500BA - Product Features




### Slim and stylish

Designed as a space-saver, this sleek 1.5 litre nettop PC only measures 3.8cm in width. It maximizes space whether it is placed upright using its stylish stand or affixed to the back of a display with the optional VESA mounting kit (PV01). Due to its small size and flexible design, this practical nettop offers exceptional functionality and is well-suited for home users, small offices, reception areas, classrooms, libraries, showrooms, call centres, public institutions and more.



### Fanless and quiet

The Shuttle XS 3500BAcomes totally fanless making it perfect to be used in noise-sensitive environments such as living rooms, hospitals, libraries etc. As an additional benefit, fanless cases rarely gather dust on the inside and stay cleaner than others. So it's not only quiet and low in energy use, but also dust-free and virtually maintenance free.



### The new Atom processor integrates the graphics controller

Shuttle XS 3500BA is equipped with Intels new Atom processor, codenamed Pineview. It comes with both the memory controller and graphics core on-die which helps to keep heat dissipation and memory latency low. The CPU is connected to the Southbridge NM10, codenamed Tiger Point.

### Dual Core. Do more.

Shuttle always uses the dual-core variant of Intel's Atom processors and thus integrates the Atom D510. This boosts the system performance significantly with particular regards to multi-threaded applications.



### Highly energy-saving

The X\$ 3500BA barely consumes, depending on system load, about  $16{\sim}20$  Watts. Running the device\*) 5 days a week for eight hours a day, the annual consumption would amount to less than 40kWh which would mean just 8 Euros on the power bill (20 Euro ct/kWh) - way less than a conventional desktop PC draws.

\*) Based on a configuration with 2GB of memory, 160GB hard disk and Windows 7



### SD card reader

The built-in SD card reader at the front side makes it easy to transfer files from your camera so you can share videos and photos on your XS 3500BA with ease.



### **Kensington Lock**

This is a small, metal-reinforced hole as part of an anti-theft system. As known from notebooks, this Mini-PC can also be safely locked by tieing it to a solid object.

(The lock-and-cable apparatus is not included.)



### Optional VESA mount (Accessory PV01)

Its optional VESA75/100 wallmount allows it to be installed on to walls or just affixed on the rear side of a monitor which is particularly interesting for the industry segment, company buildings and public institutions.

ses only.
burbos
ustration
s for ill
Picture
nout notice.
ange witl
ct to cha
n subje
nformatic
y). All i
(German
dels GmbH
nputer Han
Shuttle Corr
©2010 by

	Shuttle XS 3500BA Specifications				
Chassis	Dimensions without stand: 25.2 x 16.2 x 3.85 cm (DxHxW) = 1,57 litre Dimensions with stand: 25.2 x 18.5 x 10.04 cm (DxHxW)  Hole for the Kensington Lock at the back panel  Optional accessory: 75mm and 100mm VESA mounting kit (PV01)  Warning: Please make sure the system is always placed upright using either its stand or the optional VESA mount.  Ventilation holes must not be blocked to ensure sufficient cooling.				
Operation System	Microsoft Windows 7 Professional 9 languages available: German, English, French, Dutch, Italian, Spanish, Swedish, Finnish, Danish				
Processor	Intel Dual-Core Atom processor D510 (Codename: Pineview-D) 45nm manufacturing process, FCBGA559 Intel Hyper-Threading technology: 2-threads per core Intel 64 architecture, Core clock: 1.66GHz L2 Cache: 1024kB, TDP: max. 15W Integrated North Bridge with controller for memory and graphics				
Cooling	Passive, completely fanless cooling				
Chipset	Intel® NM10 Express Chipset Platform Controller Hub (PCH), Code name: Tiger Point				
BIOS	AMI BIOS in a 2Mbit Flash ROM supports PnP, ACPI 3.0 Supports external USB flash memory card boot up				
Memory	2048MB DDR2-667 (PC5300) One SO-DIMM module with 200 pins				
Optical drive	Open bay supports one optical drive in slimline format Serial ATA interface, 12.7mm height (optical drive not built in)				
Hard disk drive	160GB Serial ATA hard disk 6.35cm/2.5" format (5400 RPM)				
Integrated Graphics	The Graphics Processing Unit (GPU) is integrated into the processor Intel GMA 3150, 400MHz render clock frequency Intel Dynamic Vidieo Memory Technology 4.0 (DVMT 4.0) Share system memory max. 256MB Supports DirectX 9 and 2D/3D instruction set, Pixel Shader 2.0 MPEG2 hardware acceleration Intel Clear Video / ProcAmp technology allows user adjustment of hue, saturation, brightness and contrast Analog VGA: supports up to 2048x1536, 60Hz resolution				

Integrated Audio	IDT92HD81 Audio Codec with Azalia support Two analog audio connectors (3.5mm):  1) Line out (head phone)  2) microphone input				
Card Reader	Integrated card reader supports SD and SDHC memory flash cards				
Wired Network	RJ45 connector supports 10/100 Mbit/sec. PCI-Express x1 interface Supports Deep Sleep Mode (DSM) Combo controller JMC261 (for LAN and card reader)				
Wireless Network	Supports IEEE 802.11b/g/n Half size Mini-PCle-Card				
Connectors	VGA Analog Video (D-Sub 15 pol., analog) 5x USB 2.0 (1x front, 4x rear) Network (LAN, RJ45) Audio Line-out (head phone) Microphone input DC input for power adapter				
LEDs and Buttons	Power button Power LED (white) Hard disk LED (blue)				
Power supply	External 40W AC/DC power adapter (fanless) AC Input: 100~240V AC, 50~60Hz				
Certification and Compliance	EMI: CE, FCC, BSMI, C-Tick Safety: CB, BSMI, ETL Other compliances: RoHS, Eup Lot6				

## **Shuttle** XS35/GT Product Overview


Graphics	Model name	Туре	Operation System	Memory	Hard Disk	DVD R/W	Bar Code
	XS35	Barebone	_	-	-	_	811686003274
Integrated (IGP) Intel GMA3150	X\$35-703	System	_	2 GB DDR2	160 GB	_	811686007920
	XS35-704	System	_	2 GB DDR2	320 GB	Yes	811686007937
VGA	XS 3500BA	System	Win 7 Professional	2 GB DDR2	160 GB	_	4046047102181
	XS350VA	System	OpenSUSE Linux	2 GB DDR2	160 GB	-	4046047102204
Next Generation	XS35GT	Barebone	_	-	_	-	811686003281
	X\$35GT-804	System	_	2 GB DDR2	500 GB	Yes	811686007982
	XS 3510MA	System	Win 7 Home Premium	2 GB DDR2	500 GB	Yes	4046047102198

### Shuttle XS 3500BA - Connectors

### **Front Panel**

# 2

### **Back Panel**



- 1 SD card reader
- 2 USB connector
- 3 Power button with power and hard disk LED
- 4 Stand

- A Microphone input
- **B** Head phone output (line out)
- C Network connector (RJ45)
- D 4x USB connectors
- E Hole for the Kensington lock
- F VGA connector
- G Connector for power adapter
- **H** Stand

\*) Note: The optical drive is not included.



### Warning:

Please make sure the system is always placed upright using either its stand or the optional VESA mount. Ventilation holes must not be blocked to ensure sufficient cooling.



Images are only for illustration purposes. The optical drive is not included.